



- Man-less Operation
- Fresh Air In/ Fresh Air Out
 - Dry Dehumidified Breathable Air
- BOP Thawing/Heat
- Substructure Heat
- Gas Project Heat
- Facility Heat
 - Permanent or Temporary
- Maintenance Shack Heat
- Derrick Heat
- Equipment Start Up
- Field Heat Source
- Pre-heating Machinery

MA-700



Contact:

Customer Service
getheat@conleymax.com
Toll Free: 1.855.573.HEAT (4328)

North Dakota

14233 Hwy 2
Williston, ND 58801
USA
Fax: 1.855.301.8653
Phone: 701.577.HEAT (4328)

Wyoming

6713 W. Yellowstone Hwy.
Casper, WY - 82604
USA
Phone: 307.265.0456



MA-700

PERFORMANCE

Fuel		Diesel
Heater Input/Output	kBTU	700 / 630
Fuel Consumption	per hour	5.5 gal / 20 L
Efficiency	%	90+
Air Flow @ rated SP	CFM	5,000
Static Pressure @ rated RF	in./H2O	2.1
Temperature Rise	°C / °F	170 / 77

TECHNICAL DATA

Dimensions (LxWxH)	m / in.	136x68x90 / 3.45x1.73x2.3
Dry Weight	kgs / lbs.	5,640 / 2,560
Fuel Capacity		150 gal / 570 L
Maximum Run Time	hrs.	26

COMPONENTS

Engine	John Deere 4.5L
Exhaust Exchanger	Air
Fan	Belt Drive
Control System	Electronic

TRAILER

Hitch	2 5/16"
Lifting Crane Eyes	Centerpoint
Fork Lift Pockets	Yes
Axle	1
Electric Brakes	Yes
Discharge Ports	Single / 16

ALL UNITS INCLUDE SYSTEM PROTECTION PACKAGE:

Overheat, Low Oil Level, Oil Pressure, Low Fuel, and Overspeed Shut Down Valve.

SAFETY FEATURES INCLUDE:

Secondary Liquid Containment, Brushless Alternator, Positive Air Shut Off and Emergency Stop Button.

***PATENT PENDING**