



MC-710

- Air and Glycol Loop Heat
 - BOP and Rig Tank Heat
 - Simultaneous Operation
 - Control Valve
- 400 BBL Tank Insert
 - Tank Farm Heat
 - 1 Unit/ 4 tanks
- Heat Exchanger
 - Flow-back Tank Heat
 - Rig Tank Heat
 - Pond Heat
 - BOP Heat
 - Substructure Heat



Open top tank heat exchanger



400bbl heat exchanger insert



Contact:

Customer Service
sales@conleymax.com
Toll Free: 1.855.573.HEAT (4328)

ConleyMax Inc.

850 - 396 11th Ave SW
Calgary, AB T2R 0C5
Canada
Fax: 1.855.301.8653
Phone: 403.476.7011

ConleyMax Energy Inc.

14233 Hwy 2
Williston, ND 58801
USA
Fax: 1.855.301.8653
Phone: 701.577.HEAT (4328)



MC-710

PERFORMANCE

Fuel		Diesel
Air Heater	kBTU	200-700
Glycol Heater	kBTU	0-500
Fuel Consumption	per hour	17 L / 4.5 gal
Efficiency	%	91+
Air Flow @ rated SP	CFM	5,000
Static Pressure @ rated RF	in./H2O	2.1
Temperature Rise	°C / °F	77 / 170

TECHNICAL DATA

Dimensions (LxWxH)	ft / m	188x82x91 / 4.77x2.08x 2.31
Dry Weight		4,082 kgs / 9,000 lbs
Fuel Capacity		567.8 L / 150 gal
Maximum Run Time	hrs.	28
Glycol Lines	m / ft	122mx3.17 cm / 400'x1.25"

COMPONENTS

Engine		John Deere 4.5L
Exhaust Exchanger		Air/Liquid
Pump	Centrifugal	Belt Drive
Control System		Electronic
Hose wheel - out		Manual
Hose wheel - in		Electric

TRAILER

Hitch		2 5/16"
Lifting Crane Eyes		4 Points
Axle		2
Electric Brakes		Yes
Discharge Air Port	qty/dia. (in.)	Single/16
Removable Hitch for shipping		Yes

ALL UNITS INCLUDE SYSTEM PROTECTION PACKAGE:

Overheat, Low Fluid Level, Fluid Pressure, Low Fuel, and Over speed Shut Down Valve.

SAFETY FEATURES INCLUDE:

Secondary Liquid Containment, Brushless Alternator, Positive Air Shut Off and Emergency Stop Button.

*PATENT PENDING