



# MA-1200

- Unmanned Operation
- Fresh Air In/ Fresh Air Out
  - Dry Breathable Air
- BOP Thawing/Heat
- Substructure Heat
- Gas Project Heat
- Facility Heat
  - Permanent or Temporary
- Maintenance Shack Heat
- Derrick Heat
- Equipment Start Up
- Field Heat Source
- Preheating Machinery



**Contact:**  
Customer Service  
sales@conleymax.com  
Toll Free: 1.855.573.HEAT (4328)

**ConleyMax Energy Inc.**  
14233 Hwy 2  
Williston, ND 58801  
USA

Fax: 403.476.7011  
Phone: 701.577.4328

**ConleyMax Inc.**  
850 – 396 11<sup>th</sup> Ave SW  
Calgary, AB T2R 0C5  
Canada

Fax: 403.476.7011  
Phone: 403.476.7011



# MA-1200

## PERFORMANCE

Fuel		Diesel
Heater Rating	MBTU	1.2
Fuel Consumption	per hour	37.8 L / 10.0 gal
Efficiency	%	90+
Air Flow @ rated SP	CFM	2 x 7,000
Static Pressure @ rated RF	in./H2O	5.5
Temperature Rise	°C / °F	109 / 240

## TECHNICAL DATA

Dimensions (LxWxH)	m / in.	4.77x2.08x2.47 / 188x82x99
Dry Weight	kgs / lbs.	3,290 kgs / 7,240 lbs
Fuel Capacity		1,197 L / 315 gal
Maximum Run Time	hrs.	26

## COMPONENTS

Engine	John Deere 6.8L
Exhaust Exchanger	Air
Fan	Belt Drive
Control System	Electronic

## TRAILER

Hitch		2 5/16"
Lifting Crane Eyes		4 Points
Axle		2
Electric Brakes		Yes
Discharge Ports	qty/dia. (in.)	Dual / 16"

## ALL UNITS INCLUDE SYSTEM PROTECTION PACKAGE:

Overheat, Low Oil Level, Oil Pressure, Low Fuel, and Overspeed Shut Down Valve.

## SAFETY FEATURES INCLUDE:

Secondary Liquid Containment, Brushless Alternator, Positive Air Shut Off and Emergency Stop Button.

**\*PATENT PENDING**