



# MA-700

- Unmanned Operation
- Fresh Air In/ Fresh Air Out
  - Dry Breathable Air
- BOP Thawing/Heat
- Substructure Heat
- Gas Project Heat
- Facility Heat
  - Permanent or Temporary
- Maintenance Shack Heat
- Derrick Heat
- Equipment Start Up
- Field Heat Source
- Preheating Machinery



**Contact:**  
Customer Service  
sales@conleymax.com  
Toll Free: 1.855.573.HEAT (4328)

**ConleyMax Inc.**  
850 – 396 11<sup>th</sup> Ave SW  
Calgary, AB T2R 0C5  
Canada  
Fax: 1.855.301.8653  
Phone: 403.476.7011

**ConleyMax Energy Inc.**  
14233 Hwy 2  
Williston, ND 58801  
USA  
Fax: 1.855.301.8653  
Phone: 701.577.HEAT (4328)



# MA-700

## PERFORMANCE

Fuel		Diesel
Heater Input/Output	kBTU	700 / 630
Fuel Consumption	per hour	13.25 L / 3.5 gal
Efficiency	%	90+
Air Flow @ rated SP	CFM	5,000
Static Pressure @ rated RF	in./H2O	2.1
Temperature Rise	°C / °F	77 / 170

## TECHNICAL DATA

Dimensions (LxWxH)	m / in.	3.35x1.93x1.78 / 132x76x70
Dry Weight	kgs / lbs.	2,025 / 4,500
Fuel Capacity		378 L / 100 gal
Maximum Run Time	hrs.	28

## COMPONENTS

Engine	John Deere 3.0L
Exhaust Exchanger	Air
Fan	Belt Drive
Control System	Electronic

## TRAILER

Hitch		2 5/16"
Lifting Crane Eyes		Centerpoint
Fork Lift Pockets		Yes
Axle		1
Electric Brakes		Yes
Discharge Ports	qty/dia. (in.)	Single / 16

## ALL UNITS INCLUDE SYSTEM PROTECTION PACKAGE:

Overheat, Low Oil Level, Oil Pressure, Low Fuel, and Overspeed Shut Down Valve.

## SAFETY FEATURES INCLUDE:

Secondary Liquid Containment, Brushless Alternator, Positive Air Shut Off and Emergency Stop Button.

**\*PATENT PENDING**