



RT-350

- Unmanned Operation
- Fresh Air In/ Fresh Air Out
 - Dry Breathable Air
- BOP Thawing/Heat
- Substructure Heat
- Gas Project Heat
- Facility Heat
 - Permanent or Temporary
- Maintenance Shack Heat
- Derrick Heat
- Equipment Start Up
- Field Heat Source
- Preheating Machinery



Contact:
Customer Service
sales@conleymax.com
Toll Free: 1.855.573.HEAT (4328)

ConleyMax Inc.
850 - 396 11th Ave SW
Calgary, AB T2R 0C5
Canada
Fax: 1.855.301.8653
Phone: 403.476.7011

ConleyMax Energy Inc.
14233 Hwy 2
Williston, ND 58801
USA
Fax: 1.855.301.8653
Phone: 701.577.HEAT (4328)



RT-350

PERFORMANCE

Fuel		Diesel
Heater Input/Output*	kBTU	350 / 315
Fuel Consumption	per hour	9.5 L / 2.5 gal
Efficiency	%	90+
Air Flow @ rated SP**	CFM	1,750
Static Pressure @ rated RF	in./H2O	2
Temperature Rise	°C / °F	93.3 / 200

*BTU Calculated using 138,000 BTU/gal. diesel

**Airflow and SP are measured after discharge with 16"x16' pipe

TECHNICAL DATA

Dimensions (LxWxH)	m / in.	2.74x1.75x1.78 / 108x69x70
Dry Weight	kgs / lbs.	1,134 / 2,500
Fuel Capacity		302.8 L / 80 gal
Maximum Run Time	hrs.	32

COMPONENTS

Engine	Isuzu
Exhaust Exchanger	Air/Air
Control System	Electronic

TRAILER

Hitch		2 5/16"
Lifting Crane Eyes		Centerpoint
Fork Lift Pockets		No
Axle		1
Electric Brakes		Yes
Discharge Ports	qty / dia. (in.)	Single / 12

ALL UNITS INCLUDE SYSTEM PROTECTION PACKAGE:

Overheat, Low Oil Level, Oil Pressure, Low Fuel, Overspeed Shut Down Valve/Positive Air Shut Off and Brushless Alternators.

SAFETY FEATURES INCLUDE:

Secondary Liquid Containment, Monitoring Beacon, and Emergency Stop Button.